

Speedlite 470EX-AI		
POWER		
	Guide No. (ISO100).meters	47
ZOOM		
	Zoom head	Yes
	focal length coverage	24-105mm
	Coverage with wide panel	14mm
	Auto zoom for sensor size	Yes
FLASH MODES		
	Auto exposure control	E-TTLII/E-TTL/TTL
	High speed sync (FP)	Yes
	Manual / output settings	Yes - 1/1- 1/128
	Manual steps	1/3 step
	Strobe / output settings	-
	Frequency	-
	Video light	-
	Video light power	-
	Video light colour temperature	-
FLASH-RELATED FUNCTION		
	FE lock	Yes
	Flash exposure compensation	Yes
	Flash Exposure bracketing	Yes
	Second-curtain flash sync	Yes
	Modelling flash	Yes
	Colour temperature info communication	Yes
WIRELESS FLASH		
	Transmitter	No
	Transmission type	Infra-red
	Transmitter Max range approx	Indoors: 10m Outdoors: 6m / 10m
	Receiver	Yes
	No of groups	3
	No of channels	4
	Remote Shutter Release	-
FLASH HEAD MOVEMENT		
	Up	0°-120°
	Down	-
	Left	0°-180°
	Right	0°-180°
	AI Bounce	Yes (AI Bounce full auto, AI Bounce semi auto)
AF ASSIST		
	AF-assist beam	Yes
	Number of AF points supported	1 - 16 (28mm or longer focal length)
	AF-assist beam type	Infra-red / flash strobe
POWER SOURCE		
	Battery	4 x AA batteries
	Minimum recycling time *2	Approx. 5.5sec
	External power supply	-
CONSTRUCTION		
	Dust and water resistance	No
	Mounting foot material	Metal
MISC.		
	Custom function	10 (24 options) + 9 personal functions
	Flash settings from camera menus *3	Yes
	External flash exposure sensor	No
	PC terminal	No
	Compatible Accessories	Bounce adapter SBA-E4 Off-camera shoe cord OC-E3 EX Series Speedlite or camera with optical sender function
	Dedicated flash bracket	No
DIMENSIONS & WEIGHT		
	Size (W x H x D), mm	74.6 x 130.4 x 105.1
	Weight (Excluding batteries), grams	385g
FOOTNOTES		
*2 time taken to recharge flash after full discharge using Alkaline AA batteries		
*3 With compatible cameras only		